



RING TYPE TENSION LOAD CELL

LC-RTT

IEICOS Ring Type Tension Load Cell for measurement of tensile loads. It is manufactured from high grade stainless steel and is available from 100 Kgf to 100T capacity. Loads have to applied symmetrically at the top and a hardened steel eyebolts to ensure minimal error due to eccentric load effects.



Wiring Scheme

Red + (Input +) Yellow - (Output -) Black - (Input -) Green + (Output +)

Performance Specification

Standard Capacities	100 Kg, 200 Kg, 500 Kg, 1T, 2T, 5T, 10T, 20T, 50T, 100T
Excitation Voltage	10 VDC - Maximum 15 VDC
Nominal Output	0.25 - 1 mV/ V
Non - Linearity	< $\pm 0.5\%$ FSO
Hysteresis	< $\pm 0.5\%$ FSO
Non-Repeatability	< $\pm 0.5\%$ FSO
Creep (30 minutes)	< $\pm 0.5\%$ FSO
Zero Balance	$\pm 1.0\%$ FSO
Input Resistance	350 ± 5 Ohms
Output Resistance	350 ± 5 Ohms
Insulation Resistance (50 VDC)	> 1000 Mega Ohms
Cable Length (4 Core Screened)	500 mm. Minimum
Safe Overload of Rated Capacity	150%
Ultimate Overload of Rated Capacity	200%
Temp. Compensated Range	0-60 $^{\circ}$ C
Temperature Effect on Output	< 0.0015% FSO/ $^{\circ}$ C
Temperature Effect on Zero	< 0.0020% FSO/ $^{\circ}$ C

INDUSTRIAL ENGINEERING INSTRUMENTS

Manufacturers of Techno Electronic Aids Devices, Instruments and Systems,

203, 12th Main Road, 3rd Phase, Peenya Industrial Area,

Peenya, Bangalore-560058. Karnataka, India.

Phone : 91-80-28394520 Fax : 91-80-28371386

Email: info@ieicos.com Web Site: www.ieicos.com

Due to continuous improvement, specifications, dimensions, look, color, feel and features subject to change without notice.